

Technical Data

Product: Central Vacuum Supply System CVS 500 – incl. 3 x SOGEVAC SV 65 B
Part No.: 504312V050

Volume vacuum vessel:	500 l
Installed vacuum pump:	3 x SOGEVAC SV 65 B
Inlet connection vacuum vessel:	G 2", Inside thread
Outlet connection:	G 1 1/4", Inside thread
Nominal pumping speed at 50 Hz:	177 m ³ /h
Nominal pumping speed at 60 Hz:	213 m ³ /h
Pumping speed at 50 Hz:	162 m ³ /h
Pumping speed at 60 Hz:	192 m ³ /h
Ultimate total pressure without gas ballast:	≤ 0,5 mbar
Ultimate total pressure with gas ballast:	≤ 1,5 mbar
Water vapor tolerance at 50 Hz:	30 mbar
Water vapor tolerance at 60 Hz:	30 mbar
Water vapor capacity at 50 Hz:	3000 g/h
Water vapor capacity at 60 Hz:	3750 g/h
Operating fluid:	LVO 130
Operating fluid capacity:	6 l
Noise level to DIN 45 635:	65 dB(A), without gas ballast
Mains connection:	3-ph, 400 V, 50 Hz // 460 V, 60 Hz
Installed motor rating at 50 Hz:	4,5 kW
Installed motor rating at 60 Hz:	5,4 kW
Electrical control:	Full Feature-Controller
Admissible ambient temperature:	+12 to +40°C
Dimensions (LxBxD):	1976 x 833 x 1431 mm
Weight:	560 kg

Technical data are subject to change